# Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II and Commission Regulation (EU) 2015/830



Version 1.0: 03.05.2019

# **ZAP Grease BROWN**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1. Product Identifier**

# **ZAP Grease BROWN**

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Lithium extreme pressure (EP) lubricating grease.

## 1.3. Details of the supplier of the safety data sheet

ZAP LUBES SIA,

5 VISKALU STREET LV-1026 RIGA, LATVIA Phone: + 371 67543642 e-mail: <u>sales@zap-grease.com</u> www.zap-grease.com

#### **1.4. Emergency telephone number**

State Fire And Rescue Service Of Latvia: +371 112 Valsts Toksikoloģijas Centrs (National Toxicology Center), **Saindēšanās un zāļu informācijas centrs** (Poisoning and Drug Information Centre) Address: Hipokrāta 2, LV-1038 Riga, Latvia, Phone: +371 67042473, service is available 24 hours

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 (CLP)

#### Not classified.

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

## 2.2. Label elements

Labelling according to Regul	lation (EC) No 1272/2008 (CLP)
Hazard pictograms	Not applicable.
Signal word	Not applicable.
Hazard Statements	Not applicable.
Precautionary statements	Not applicable.
Voluntary precautionary advice	S
- in general	Keep out of reach of children (P102).
- for prevention	Wash skin thoroughly after handling (P264)
	Wear protective gloves/protective clothing/eye protection/face protection (P280)
- in reaction	Take off contaminated clothing (P362)
- at storage	None
- for disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations (P501).
Supplemental label elements	EUH210 Safety Data Sheet available on request.

#### 2.3. Other hazards

The product does not contain any substance which meets the criteria for PBT and vPvB in accordance with Annex XIII.



# SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

Mixture Description

Lithium extreme pressure (EP) lubricating grease.

Substance name	%, weight	REACH Registration No.	EINECS/CAS No	Classification according to regulation (EC) No 1272/2008 (CLP)
Lubricating oils (petroleum), C24-50, solvent-ext., dewaxed, hydrogenated	< 93	01-2119489969-06	309-877-7/101316-72-7	Not classified.
Zinc dialkyl dithiophosphate	< 1	*	272-028-3/68649-42-3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

#### **NOTES:**

All mineral oils are considered to be severely refined and not considered to be carcinogenic under IARC. All the oils in this product contain < 3% DMSO extract (IP 346).

\* Not available or substance is not currently required for registration under REACH.

For a full text of relevant hazard statements, hazard classes and category codes: See SECTION 16.

# SECTION 4: First aid measures

4.1.	Description of first aid measures			
	Inhalation	If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.		
	Skin contact	Wash skin with plenty of soap and water for several minutes. Get medical		
		attention if skin irritation develops or persists.		
	Eye contact	Remove contact lenses before flushing, if any and easy to do. Immediately flush eyes with plenty of clean water keeping eyelids apart. Get medical attention if eye irritation persists.		
	Ingestion	DO NOT INDUCE VOMITING. Get medical attention. Never give anything by mouth		
		to an unconscious or convulsing person.		
	Need of immediate medical attention	If nausea or irritations do not appear after ingestion, give medical carbon in water slurry (3 tablespoons in one litre water).		
4.2.	Most important symptoms ar	nd effects, both acute and delayed		
		Prolonged inhalation of unusually high concentrations of product mist or vapours		
		may cause nose and lung irritation, headache, nausea and drowsiness.		
		Prolonged or repeated skin contact may produce allergic reactions such as		
		redness, rash and dermatitis.		
		Prolonged eye contact may cause irritation, redness and discomfort.		
		If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.		
4.3.	Indication of any immediate	medical attention and special treatment needed		
		Treat symptomatically.		
SECTI	ON 5: Firefighting measures			
5.1.	Extinguishing media			
	Suitable Extinguishing media	Use water fog, dry powder, foam or carbon dioxide. Use water to cool fire- exposed containers. If the leak or spill has not ignited, use water fog to disperse the vapours and to provide protection for personnel attempting to stop the leak.		
	Unsuitable Extinguishing media	Water jet		
	Version 1.0			
	03.05.2019	ZAP Grease BROWN Page: 2 of 8		

# 5.2. Special hazards arising from the substance or mixture

Smoke, carbon monoxide, carbon dioxide and other products of incomplete combustion.

#### 5.3. Advice for firefighters

Special protective equipment	The nature of special protective equipment required will depend upon the size of
for firefighters	the fire, the degree of confinement of the fire and the natural ventilation
	available. Fire-resistant clothing and self-contained breathing apparatus is
	recommended for fires in confined spaces and poorly ventilated areas. Full
	fireproof clothing is recommended for any large fires involving this product.
Extinguishing procedures	In case of fire - always call the fire brigade. Small fires, such as those capable of
	being fought with a hand-held extinguisher, can normally be fought by a person
	who has received instruction on the hazards of flammable liquid fires. Fires that
	are beyond that stage should only be tackled by people who have received hands-
	on training. Ensure escape path's available.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

	For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
	For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2.	Environmental precautions	Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.
6.3.	Methods and material for con	tainment and cleaning up Clean-up spill as soon as possible while following the requirements for exposure control/personal protection. Use sand and sawdust to clean. Use appropriate cleaning techniques such absorption by fire resistant material or pumping.
6.4.	Reference to other sections	See Section 8 for more information on personal protective equipment. See Section 13 for waste disposal practices.

# SECTION 7: Handling and storage

7.1.	Precautions for safe handling	
		Avoid prolonged or repeated contact with skin. Avoid breathing of vapours. Wash hands after handling. Do not smoke.
7.2.	Conditions for safe storage, in	cluding any incompatibilities
		Keep containers closed when not in use. Avoid exposure to heat. Store at ambient temperature. Do not store near explosive substances, compressed, liquefied or pressurized gases, flammable liquids or oxidizing agents.
7.3.	Specific end use(s)	In accordance with the relevant product specification.

Version 1.0 03.05.2019



1.	<b>Control parameters</b> Occupational exposure limits	Union occupational exposure limit values do not refer to any components of a
		mixture specified in Section 3.
		Please refer to National occupational exposure limits, if applicable.
2.	Exposure controls	
	Appropriate engineering controls	Use in well-ventilated areas.
	Individual protection measures, such as personal protective equipment	Follow the good occupational and personal hygiene practices to control product exposures.
	Eye/face protection	Safety goggles.
	Hand protection	Neoprene gloves. Time for wearing out the gloves material >30 minutes.
	Skin/body protection	Exposed employees should exercise reasonable personal cleanliness. This include cleansing exposed skin areas several times daily with soap and water and laundering or dry cleaning soiled work clothing. Long sleeve shirt is recommended. Use chemically protective boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction.
	Respiratory protection	No respiratory protection is normally required. If vapour or mist is generated, use approved respirator as appropriate.
	Thermal hazards	Not available.
	Hygiene measures	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
	Environmental exposure control	May form an oil film leading to de-oxygenation of water and possible harmful effect on aquatic life.
		Product can penetrate soil until reaching the surface of ground water (in the presence of ground water).

# SECTION 9: Physical and chemical properties

.1.	Information on basic physical and chemical properties		
	Appearance	Semi-solid	
	Colour	Yellow-brown	
	Odour	Petroleum	
	Odour threshold	Not applicable	
	рН	Not applicable	
	Freezing/Pour point, °C	Not applicable	
	Initial boiling point and boiling range, °C	Not applicable	
	Flash point, °C (Pensky-Martens Closed Cup)	>230 for base oil	
	Evaporation rate	No data available	
	Flammability (solid, gas)	Not applicable	
	Upper/lower flammability or exposure limits	Not applicable	
	Vapour pressure	Not applicable	
	Vapour density	Not applicable	



	Relative density at 20°C, g/ml	<1
	Solubility	Soluble in hydrocarbons, insoluble in water
	Partition coefficient: n-octanol/water	No data available
	Auto-ignition temperature, °C	Not applicable
	Decomposition temperature, °C	Not applicable
	Kinematic viscosity, mm <sup>2</sup> /s	100 mm <sup>2</sup> /s at 40°C (for base oil)
	Explosive properties	None
	Oxidising properties	None
9.2.	Other Information	
	Dropping point, °C	>180

## SECTION 10: Stability and reactivity

**10.1. Reactivity:** Not expected to enter reactions.

- **10.2.** Chemical stability: This product is considered chemically stable at normal storage and handling conditions.
- 10.3. Possibility of hazardous reactions: None
- **10.4.** Conditions to avoid: This product is normally stable at moderately elevated temperatures and pressures.
- **10.5.** Incompatible materials: Strong oxidizing agents, strong acids.
- **10.6.** Hazardous decomposition products: None known.

# SECTION 11: Toxicological information

1	Information on toxicological effects		
	Acute toxicity	Based on data available for base oils: the classification criteria are not met. LD <sub>50</sub> oral (rats) > 5000 mg/kg (OECD 401) LD <sub>50</sub> dermal (rabbits) > 5000 mg/kg (OECD 402) LC <sub>50</sub> inhalation (rats) > 5 mg/l/4h (OECD 403)	
	Skin corrosion/irritation	Not expected to cause skin corrosion or irritation. Repeated or prolonged contact with skin may defat or dry the skin resulting in discomfort and dermatitis.	
	Serious eye damage/irritation	Not expected to cause serious eye damage or irritation. May cause eyes irritation. May cause minimal irritation or redness if accidental eye contact occurs.	
	Respiratory or skin sensitisation	Not expected to be respiratory or skin sensitizer. Prolonged or repeated skin contact as from clothes wetted with material may cause dermatitis.	
	Germ cell mutagenicity	No data available to indicate product or any components present at levels greater than 0.1% are mutagenic or genotoxic.	
	Carcinogenicity	This product is not considered to be a carcinogenic by IARC, ACGIH, NTP or OSHA. Nota L – meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound using IP 346.	
	Reproductive toxicity	Not expected to have reproductive toxicity. Based on date for similar substances.	
	STOT-single exposure	Not expected to damage specific target organs. Based on date for similar substances.	
`	Version 1.0		



STOT-repeated exposure	Not expected to damage specific target organs. Based on date for similar substances.
Aspiration hazard	The mixture does not meet the criteria for classification.
Other information	If material is misted or if vapours are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.

# SECTION 12: Ecological information

	0	
12.1	Toxicity	This product is of relatively low toxicity – based on data of product components. $LC_{50}$ for base oil (96 hours for fish) is > 100 mg/l (OECD 203) $EC_{50}$ for base oils (48 hours for Daphnia) is > 10 000 mg/l (OECD 202) $EC_{50}$ for base oils (72-96 hours for algae or other aquatic plants) > 100 mg/l (OECD 201) NOEL/21 days (aquatic invertebrates) > 10 mg/l (OECD 211) NOEL/72 h (algae) > 100 mg/l NOEL/10 min (micro organisms) > 1.93 mg/l (DIN 38412, DIN 38409)
12.2	Persistence and degradability	This product is not readily biodegradable. Information about base oil-Inherent biodegradability <22% after 28 days (OECD 301B).
12.3	Bioaccumulative potential	Partition coefficient n-octanol/water (log K <sub>ow</sub> ) for base oils is > 4.0 - indicates possible bioaccumulation.
12.4	Mobility in soil	Low, due to low water solubility. Spillage may penetrate the soil causing ground water contamination.
12.5	Results of PBT and vPvB asse	<b>ssment</b> This product is not and does not contain any substance that is potential PBT or vPvB.
12.6	Other adverse effects	May form an oil film leading to deoxygenation of water and possible harmful effect on aquatic life.
SECTI	ON 13: Disposal consideration	n
13.1	Waste treatment methods	Dispose of empty lubricant containers at approved for such wastes places. Follow all state or local regulations and requirements for disposal, recycle or reclaiming or waste oils and petroleum products.
	Waste Code	13 08 99* in accordance with European Waste Catalogue (E. W. C.)
SECTI	ON 14: Transport informatior	1
14.1	UN Number	None
14.2	UN proper shipping name	Not applicable.
14.3	Transport hazard class(es)	None
14.4	Packing group	Not applicable.
14.5	<b>Environmental hazards</b> ADR RID	Not regulated as dangerous goods.



IMDG IATA Not regulated as dangerous goods. Not regulated as dangerous goods.

#### 14.6 Special precautions to user None

**14.7** Transport in bulk according to Annex II of Marpol and the IBC code Not applicable.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of The European Parliament And Of The Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1272/2008 of The European Parliament And Of The Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

#### 15.2 Chemical safety assessment

Not available.

## SECTION 16: Other information

Indication of which of the methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 was used for the purpose of classification.

Classification in accordance with regulation (EC) No 1272/2008:	Evaluation method used:
None.	Classification according to calculation procedure.
Revision Information Revision by sections	New SDS prepared according to Commission Regulation (EU) 2015/830.
Issue date	03.05.2019
List of abbreviations	
PBT	Persistent, Bioaccumulative, and Toxic
vPvB	very Persistent and very Bioaccumulative
LD <sub>50</sub>	Lethal Dose 50 (median concentration of a toxicant that will kill 50% of the test animals within a designated period)
LC <sub>50</sub>	Lethal Concentration 50 (concentration in water having 50% chance of causing death to aquatic life)
EC <sub>50</sub>	Half maximal effective concentration
NOEL	No-Observed-Effect Level
STOT	Specific Target Organ Toxicity

#### A list of relevant hazard statements, hazard classes and category codes



H315 - Causes skin irritation H318 - Causes serious eye damage H411 - Toxic to aquatic life with long lasting effects Eye Dam. 1 - Serious eye damage - Hazard Category 1

Skin Irrit. 2 - Skin irritation - Hazard Category 2

Aquatic Chronic 2 - Aquatic hazard (long-term) - Hazard Category 2

This information is the best of our current knowledge, and is believed to be correct as of the date hereof, and is intended to describe the product only in terms of health and safety and environmental requirements. Since the conditions of use are outside our control, any recommendations and suggestions are made without guarantee.

End of safety data sheet

