Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II and Commission Regulation (EU) 2015/830



Version 1.0: 2017-02-24

ZAP Grease COMPLEX Green

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier:

ZAP Grease COMPLEX Green

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Lithium Complex lubricating grease.

1.3. Details of the supplier of the safety data sheet:

ZAP LUBES SIA,

5 VISKALU STREET LV-1026 RIGA, LATVIA Phone: + 371 67543642 e-mail: sales@zap-grease.com www.zap-grease.com

1.4. Emergency telephone number:

State Fire And Rescue Service Of Latvia: +371 112

Valsts Toksikoloģijas Centrs (National Toxicology Center), Saindēšanās un zāļu informācijas centrs

(Poisoning and Drug Information Centre) Address: Hipokrāta 2, LV-1038 Riga, Latvia,

Phone: +371 67042473, service is available 24 hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Not classified.

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Hazard pictograms

Signal word

Hazard Statements

Precautionary statements

Not applicable.

Not applicable.

Not applicable.

Voluntary precautionary advices

- in general Keep out of reach of children (P102).

- for prevention Wash skin thoroughly after handling (P264).

Wear protective gloves/protective clothing/eye protection/face protection (P280).

- in reaction Take off contaminated clothing (P362).

- at storage None

- for disposal Dispose of contents/container in accordance with all local, regional, national and

international regulations (P501).

Supplemental label elements EUH210 Safety Data Sheet available on request.

2.3. Other hazards

The product does not contain any substance which meets the criteria for PBT and vPvB in accordance with Annex XIII.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

Mixture Description Lithium Complex lubricating grease.

Substance name	%, weight	REACH Registration No.	EINECS/CAS No	Classification according to regulation (EC) No 1272/2008 (CLP)		
Distillates (petroleum), hydrotreated heavy paraffinic	< 60	01-2119484627-25-0035	265-157-1/64742-54-7	Not classified		
Residual oils (petroleum), hydrotreated	< 50	01-2119489287-22-0007	265-160-8 / 64742-57-0	Not classified		
Distillates (petroleum), hydrotreated heavy naphthenic**	< 25	01-2119467170-45-0031 01-2119467170-45-0017	265-155-0 / 64742-52-5	Not classified		
PTFE (Polytetrafluoroethylene)	< 5	*	618-337-2 / 9002-84-0	Not classified		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	< 1	*	272-028-3 / 68649-42-3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411		
Long-chain alkenyl succinimide	< 0.2	*	Proprietary	Not classified		

NOTES:

All mineral oils are considered to be severely refined and not considered to be carcinogenic under IARC. All the oils in this product contain < 3% DMSO extract (IP 346).

For a full text of H-statements: See SECTION 16

SECTION 4: First aid measures

Description of first aid measures 4.1.

Inhalation	If irritation,	headache,	nausea, c	or drowsiness	occurs,	remove to	fresh air.	Get
------------	----------------	-----------	-----------	---------------	---------	-----------	------------	-----

medical attention if breathing becomes difficult or symptoms persist.

Skin contact Wash skin with plenty of soap and water for several minutes. Get medical

attention if skin irritation develops or persists.

Eye contact Remove contact lenses before flushing, if any and easy to do. Immediately flush

eyes with plenty of clean water keeping eyelids apart. Get medical attention if eye

irritation persists.

Ingestion DO NOT INDUCE VOMITING. Get medical attention. Never give anything by mouth

to an unconscious or convulsing person.

Need of immediate medical

If nausea or irritations do not appear after ingestion, give medical carbon in water attention

slurry (3 tablespoons in one liter water).

4.2. Most important symptoms and effects, both acute and delayed

Prolonged inhalation of unusually high concentrations of product mist or vapours

may cause nose and lung irritation, headache, nausea and drowsiness.

Prolonged or repeated skin contact may produce allergic reactions such as

redness, rash and dermatitis.

Prolonged eye contact may cause irritation, redness and discomfort.

If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and

diarrhea may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically



^{*} Not available or substance is not currently required for registration under REACH

^{**} Product contains one or more of the REACH registration Numbers

SECTION 5: Firefighting measures

5.1. Extinguishing media

exposed containers. If the leak or spill has not ignited, use water fog to disperse the vapours and to provide protection for personnel attempting to stop the leak.

Unsuitable Extinguishing media Water jet

5.2. Special hazards arising from the substance or mixture

Smoke, carbon monoxide, carbon dioxide and other products of incomplete combustion.

5.3. Advice for firefighters

Special protective equipment

for firefighters

The nature of special protective equipment required will depend upon the size of the fire, the degree of confinement of the fire and the natural ventilation available. Fire-resistant clothing and self-contained breathing apparatus is recommended for fires in confined spaces and poorly ventilated areas. Full fireproof clothing is recommended for any large fires involving this product

Extinguishing procedures

In case of fire - Always call the fire brigade. Small fires, such as those capable of being fought with a hand-held extinguisher, can normally be fought by a person who has received instruction on the hazards of flammable liquid fires. Fires that are beyond that stage should only be tackled by people who have received hands-on training. Ensure escape path's available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2. Environmental precautions

Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.

6.3. Methods and material for containment and cleaning up

Clean-up spill as soon as possible while following the requirements for exposure control/personal protection. Use sand and sawdust to clean. Use appropriate cleaning techniques such absorption by fire resistant material or pumping.

6.4. Reference to other sections

See Section 8 for more information on personal protective equipment. See Section 13 for waste disposal practices.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid breathing of vapours. Wash hands after handling. Do not smoke.

Revision No. 1 24.02.2017



7.2. Conditions for safe storage, including any incompatibilities

Keep containers closed when not in use. Avoid exposure to heat. Store at ambient temperature. Do not store near explosive substances, compressed, liquefied or

pressurized gases, flammable liquids or oxidizing agents.

7.3. Specific end use(s) In accordance with the relevant product specification.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Occupational exposure limits Union occupational exposure limit values do not refer to any components of a

mixture specified in Section 3.

Please refer to National occupational exposure limits, if applicable.

8.2. **Exposure controls**

Appropriate engineering

controls

Use in well-ventilated areas.

Individual protection measures, such as personal protective

equipment

Follow the good occupational and personal hygiene practices to control product

exposures.

Eye/face protection

Safety goggles

Hand protection Neoprene gloves. Time for wearing out the gloves material >30 minutes.

Skin/body protection

Exposed employees should exercise reasonable personal cleanliness. This includes cleansing exposed skin areas several times daily with soap and water and laundering or dry cleaning soiled work clothing. Long sleeve shirt is recommended. Use chemically protective boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could

entrap the material and cause a skin reaction.

Respiratory protection No respiratory protection is normally required. If vapour or mist is generated, use

approved respirator as appropriate.

Thermal hazards Not available

Hygiene measures When using, do not eat, drink or smoke. Always observe good personal hygiene

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard

contaminated footwear that cannot be cleaned.

Environmental exposure

control

May form an oil film leading to de-oxygenation of water and possible harmful

effect on aquatic life.

Product can penetrate soil until reaching the surface of ground water (in the

presence of ground water).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Semi-solid Colour Green Odour Petroleum Odour threshold Not applicable рΗ Not applicable Freezing/Pour point, ^oC Not applicable

Revision No. 1 24.02.2017



Page: 4 of 8

Initial boiling point and boiling range, °C

Flash point, °C (Pensky-Martens Closed Cup)

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability or exposure limits

Vapour pressure

Vapour density

Not applicable

Not applicable

Not applicable

Relative density at 20°C, g/ml < 1

Soluble in hydrocarbons, insoluble in water

Partition coefficient: n-octanol/water
Auto-ignition temperature, °C

Decomposition temperature, °C

Not applicable

Not applicable

Kinematic viscosity, mm²/s 220 mm²/s at 40°C (for base oil)

Explosive properties None Oxidising properties None

9.2. Other Information

Dropping point, ^oC >275

SECTION 10: Stability and reactivity

10.1. Reactivity: Not expected to enter reactions.

10.2. Chemical stability: This product is considered chemically stable at normal storage and handling conditions.

10.3. Possibility of hazardous reactions: None

10.4. Conditions to avoid: This product is normally stable at moderately elevated temperatures and pressures.

10.5. Incompatible materials: Strong oxidizing agents, strong acids.

10.6. Hazardous decomposition products: None known

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on data available for base oils: the classification criteria are not met

 LD_{50} oral (rats) > 5000 mg/kg (OECD 401) LD_{50} dermal (rabbits) > 5000 mg/kg (OECD 402) LC_{50} inhalation (rats) > 5 mg/l/4h (OECD 403)

NOEL/21 days (aquatic invertebrates) > 10 mg/l (OECD 211)

NOEL/72 h (algae) > 100 mg/l

NOEL/10 min (microorganisms) > 1.93 mg/l (DIN 38412, DIN 38409)

Skin corrosion/irritation Not expected to cause skin corrosion or irritation. Repeated or prolonged contact

with skin may defat or dry the skin resulting in discomfort and dermatitis.

Serious eye damage/irritation
Not expected to cause serious eye damage or irritation. May cause eyes irritation.

May cause minimal irritation or redness if accidental eye contact occurs.

Respiratory or skin sensitisation Not expected to be respiratory or skin sensitizer. Prolonged or repeated skin

contact as from clothes wetted with material may cause dermatitis



Germ cell mutagenicity

No data available to indicate product or any components present at levels greater

than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogenic by IARC, ACGIH, NTP or OSHA.

Nota L - meets EU requirement of less than 3% (w/w) DMSO extract for total

polycyclic aromatic compound using IP 346.

Reproductive toxicity Not expected to damage specific target organs. Based on date for similar

substances.

STOT-single exposure Not expected to damage specific target organs. Based on date for similar

substances.

STOT-repeated exposure Not expected to damage specific target organs. Based on date for similar

substances.

Aspiration hazard The mixture does not meet the criteria for classification.

Other information If material is misted or if vapours are generated from heating, exposure may cause

irritation of mucous membranes and the upper respiratory tract.

SECTION 12: Ecological information

12.1 Toxicity This product is of relatively low toxicity – based on data of product components.

LC50 for base oil (96 hours for fish) is > 100 mg/l (OECD 203)

EC50 for base oils (48 hours for Daphnia) is > 10 000 mg/l (OECD 202)

EC50 for base oils (72-96 hours for algae or other aquatic plants) > 100 mg/l (OECD

201)

NOEL/21 days (aquatic invertebrates) > 10 mg/l (OECD 211)

NOEL/72 h (algae) > 100 mg/l

NOEL/10 min (microorganisms) > 1.93 mg/l (DIN 38412, DIN 38409)

12.2 Persistence and degradability This product is not readily biodegradable. Information about base oil-Inherent

biodegradability <22% after 28 days (OECD 301B)

12.3 Bioaccumulative potential Partition coefficient n-octanol/water (log K_{OW}) for base oils is > 4.0 - indicates

possible bioaccumulation.

12.4 Mobility in soil Low, due to low water solubility. Spillage may penetrate the soil causing ground

water contamination.

12.5 Results of PBT and vPvB assessment

This product is not and does not contain any substance that is potential PBT or

vPvB.

12.6 Other adverse effects May form an oil film leading to deoxygenation of water and possible harmful

effect on aquatic life.

SECTION 13: Disposal consideration

13.1 Waste treatment methods Dispose of empty lubricant containers at approved for such wastes places. Follow

all state or local regulations and requirements for disposal, recycle or reclaiming of

waste oils and petroleum products.

Waste Code 13 08 99* in accordance with European Waste Catalogue (E. W. C.)

SECTION 14: Transport information

14.1 UN Number None

14.2 UN proper shipping name Not applicable

14.3 Transport hazard class(es) None

14.4 Packing group Not applicable

14.5 Environmental hazards

ADR Not regulated as dangerous goods
RID Not regulated as dangerous goods
AND Not regulated as dangerous goods
IMDG Not regulated as dangerous goods
IATA Not regulated as dangerous goods

14.6 Special precautions to user None

14.7 Transport in bulk according to Annex II of Marpol and the IBC code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of The European Parliament And Of The Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1272/2008 of The European Parliament And Of The Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

15.2 Chemical safety assessment Not available

SECTION 16: Other information

Indication of which of the methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 was used for the purpose of classification.

Classification in accordance

with regulation (EC) No

1272/2008:

None.

Revision No. 1

Evaluation method used:

Classification according to calculation procedure.

Revision Information New SDS prepared according to Commiss

Revision by sections

New SDS prepared according to Commission Regulation (EU) 2015/830.

evision by sections

2017-02-24

Issue date 201



List of abbreviations

PBT Persistent, Bioaccumulative, and Toxic vPvB very Persistent and very Bioaccumulative

LD50 Lethal Dose 50 (median concentration of a toxicant that will kill 50% of the test

animals within a designated period)

LC₅₀ Lethal Concentration 50 (concentration in water having 50% chance of causing

death to aquatic life)

EC₅₀ Half maximal effective concentration

NOEL
STEL
Short Term Exposure Limit
TWA
Time-weighted average
H315 - Causes skin irritation
H318 Causes sorious avaidate

statements and hazard H318 - Causes serious eye damage

classes H411 - Toxic to aquatic life with long lasting effects

Eye Dam. 1 - Serious eye damage - Hazard Category 1 Skin Irrit. 2 - Skin irritation - Hazard Category 2

Aquatic Chronic 2 - Aquatic hazard (long-term) - Hazard Category 2

This information is the best of our current knowledge, and is believed to be correct as of the date hereof, and is intended to describe the product only in terms of health and safety and environmental requirements. Since the conditions of use are outside our control, any recommendations and suggestions are made without guarantee.

End of safety data sheet

