
Safety Data Sheet





Version 1.07.11_EN: 18.05.2018

ZAP Grease EXTREME VG 460 X1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier:

ZAP Grease EXTREME VG 460 X1

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Calcium Sulfonate Complex lubricating grease.

1.3. Details of the supplier of the safety data sheet:

ZAP LUBES SIA,

5 VISKALU STREET LV-1026 RIGA, LATVIA Phone: + 371 67543642 e-mail: <u>sales@zap-grease.com</u> www.zap-grease.com

1.4. Emergency telephone number:

State Fire And Rescue Service Of Latvia: +371 112 Valsts Toksikoloģijas Centrs (National Toxicology Center), **Saindēšanās un zāļu informācijas centrs** (Poisoning and Drug Information Centre) Address: Hipokrāta 2, LV-1038 Riga, Latvia, Phone: +371 67042473, service is available 24 hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Not classified.

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

2.2. Label elements

- AND COLOR	
Labelling according to Regu	lation (EC) No 1272/2008 (CLP)
Hazard pictograms	Not applicable.
Signal word	Not applicable.
Hazard Statements	Not applicable.
Precautionary statements	Not applicable.
Voluntary precautionary advice	25
- in general	If medical advice is needed, have product container or label at hand (P101).
	Keep out of reach of children (P102).
- for prevention	Wash skin thoroughly after handling (P264).
	Wear protective gloves/protective clothing/eye protection/face protection (P280).
- in reaction	Take off contaminated clothing (P362).
- at storage	None
- for disposal	Dispose of contents and container in accordance with all local, regional, national and
	international regulations (P501).
Supplemental label elements	EUH208 Contains Hydroxyalkyl carboxylic ester. May produce an allergic reaction.
	EUH210 Safety Data Sheet available on request.
Other hazards	

2.3. Other hazards

Version 1.07.11_	_EN
18.05.2018	

ZAP Grease EXTREME VG 460 X1

The product does not contain any substance which meets the criteria for PBT and vPvB in accordance with Annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture Description

Calcium Sulfonate Complex lubricating grease.

Substance name	%, weight	REACH Registration No.	EINECS/CAS No	Classification according to regulation (EC) No 1272/2008 (CLP)
Residual oils (petroleum), hydrotreated	< 70	01-2119489287-22-0007	265-160-8 / 64742-57-0	Not classified.
Lubricating oils (petroleum), C24-50, solvent-ext., dewaxed, hydrogenated	< 30	01-2119489969-06	309-877-7/101316-72-7	Not classified.
Distillates (petroleum), hydrotreated heavy naphthenic*	< 20	01-2119467170-45-0031 01-2119467170-45-0017	265-155-0 / 64742-52-5	Not classified.
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	< 1.0	01-2119491299-23-0000	270-128-1 / 68411-46-1	Aquatic Chronic 3; H412
Hydroxyalkyl carboxylic ester	< 0.7	**	***	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin. Sens. 1B; H317

NOTES:

All mineral oils are considered to be severely refined and not considered to be carcinogenic under IARC. All the oils in this product contain < 3% DMSO extract (IP 346).

* Product contains one or more of the REACH registration numbers

** Not available or substance is not currently required for registration under REACH

*** Not available

For a full text of relevant hazard statements, hazard classes and category codes: See SECTION 16

SECTION 4: First aid measures

4.1.	Description of first aid measures			
	Inhalation	If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing becomes difficult or symptoms persist.		
	Skin contact	Wash skin with plenty of soap and water for several minutes. Get medical attention if skin irritation develops or persists.		
	Eye contact	Remove contact lenses before flushing, if any and easy to do. Immediately flush eyes with plenty of clean water keeping eyelids apart. Get medical attention if eye irritation persists.		
	Ingestion	DO NOT INDUCE VOMITING. Get medical attention. Never give anything by mouth to an unconscious or convulsing person.		
	Need of immediate medical attention	If nausea or irritations do not appear after ingestion, give medical carbon in water slurry (3 tablespoons in one litre water).		
4.2.	Most important symptoms a	and effects, both acute and delayed		
		Prolonged inhalation of unusually high concentrations of product mist or vapours may cause nose and lung irritation, headache, nausea and drowsiness. Prolonged or repeated skin contact may produce allergic reactions such as redness, rash and dermatitis. Prolonged eye contact may cause irritation, redness and discomfort.		
		If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.		
4.3.	Indication of any immediate	medical attention and special treatment needed		

Treat symptomatically.

ZAP Grease EXTREME VG 460 X1

SECTION 5: Firefighting measures

Extinguishing media	
Suitable Extinguishing media	Use water fog, dry powder, foam or carbon dioxide. Use water to cool fire- exposed containers. If the leak or spill has not ignited, use water fog to disperse the vapours and to provide protection for personnel attempting to stop the leak.
Unsuitable Extinguishing media	Water jet
Special hazards arising from t	he substance or mixture
	Smoke, carbon monoxide, carbon dioxide and other products of incomplete combustion.
Advice for firefighters	
Special protective equipment for firefighters	The nature of special protective equipment required will depend upon the size of the fire, the degree of confinement of the fire and the natural ventilation available. Fire-resistant clothing and self-contained breathing apparatus is recommended for fires in confined spaces and poorly ventilated areas. Full fireproof clothing is recommended for any large fires involving this product.
Extinguishing procedures	In case of fire - Always call the fire brigade. Small fires, such as those capable of being fought with a hand-held extinguisher, can normally be fought by a person who has received instruction on the hazards of flammable liquid fires. Fires that are beyond that stage should only be tackled by people who have received hands-on training. Ensure escape path's available.
	Suitable Extinguishing media Unsuitable Extinguishing media Special hazards arising from t Advice for firefighters Special protective equipment for firefighters

SECTION 6: Accidental release measures

6.1.	Personal precautions, protect For non-emergency personnel	ive equipment and emergency procedures No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
	For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2.	Environmental precautions	Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material.
6.3.	Methods and material for con	tainment and cleaning up Clean-up spill as soon as possible while following the requirements for exposure control/personal protection. Use sand and sawdust to clean. Use appropriate cleaning techniques such absorption by fire resistant material or pumping.
6.4.	Reference to other sections	See Section 8 for more information on personal protective equipment. See Section 13 for waste disposal practices.

SECTION 7: Handling and storage

7.1. Precautions for safe handling



		Avoid prolonged or repeated contact with skin. Avoid breathing of vapours. Wash hands after handling. Do not smoke.
7.2.	Conditions for safe storage, ir	ncluding any incompatibilities
		Keep containers closed when not in use. Avoid exposure to heat. Store at ambient temperature. Do not store near explosive substances, compressed, liquefied or pressurized gases, flammable liquids or oxidizing agents.
7.3.	Specific end use(s)	In accordance with the relevant product specification.
SECTI	ON 8: Exposure controls/pers	onal protection
8.1.	Control parameters	
0.11	Occupational exposure limits	Union occupational exposure limit values do not refer to any components of a mixture specified in Section 3.
		Please refer to National occupational exposure limits, if applicable.
8.2.	Exposuro controls	
0.2.	Exposure controls Appropriate engineering controls	Use in well-ventilated areas.
	Individual protection measures, such as personal protective equipment	Follow the good occupational and personal hygiene practices to control product exposures.
	Eye/face protection	Safety goggles.
	Hand protection	Neoprene gloves. Time for wearing out the gloves material >30 minutes.
	Skin/body protection	Exposed employees should exercise reasonable personal cleanliness. This includes cleansing exposed skin areas several times daily with soap and water and laundering or dry cleaning soiled work clothing. Long sleeve shirt is recommended. Use chemically protective boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction.
	Respiratory protection	No respiratory protection is normally required. If vapour or mist is generated, use approved respirator as appropriate.
	Thermal hazards	Not available.
	Hygiene measures	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
	Environmental exposure control	May form an oil film leading to de-oxygenation of water and possible harmful effect on aquatic life.
		Product can penetrate soil until reaching the surface of ground water (in the presence of ground water).

SECTION 9: Physical and chemical properties

9.1.	Information on basic phys	sical and chemical properties	
	Appearance	Semi-solid	
	Colour	Brown	
	Odour	Petroleum	
	Odour threshold	Not applicable	
	Version 1.07.11_EN		
	18.05.2018	ZAP Grease EXTREME VG 460 X1	Page: 4 of 8

Not applicable
Not applicable
Not applicable
>230 for base oil
No data available
Not applicable
Not applicable
Not applicable
Not applicable
<1
Soluble in hydrocarbons, insoluble in water
No data available
Not applicable
Not applicable
460 mm ² /s at 40°C (for base oil)
None
None
>305

SECTION 10: Stability and reactivity

9.2.

10.1. Reactivity: Not expected to enter reactions.

- **10.2.** Chemical stability: This product is considered chemically stable at normal storage and handling conditions.
- 10.3. Possibility of hazardous reactions: None
- **10.4.** Conditions to avoid: This product is normally stable at moderately elevated temperatures and pressures.
- **10.5.** Incompatible materials: Strong oxidizing agents, strong acids.
- **10.6.** Hazardous decomposition products: None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

/ersion 1.07.11_EN 8.05.2018	ZAP Grease EXTREME VG 460 X1	Page: 5 of 8
Germ cell mutagenicity	No data available to indicate product or any components	present at levels greate
Respiratory or skin sensitisation	The mixture does not meet the criteria for classification. Contains Hydroxyalkyl carboxylic ester. May produce an a	Illergic reaction.
Serious eye damage/irritation	Not expected to cause serious eye damage or irritation. N May cause minimal irritation or redness if accidental eye	, ,
Skin corrosion/irritation	Not expected to cause skin corrosion or irritation. Repeat with skin may defat or dry the skin resulting in discomform	
Acute toxicity	Based on data available for base oils: the classification cri LD ₅₀ oral (rats) > 5000 mg/kg (OECD 401) LD ₅₀ dermal (rabbits) > 5000 mg/kg (OECD 402) LC ₅₀ inhalation (rats) > 5 mg/l/4h (OECD 403)	teria are not met.

	than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogenic by IARC, ACGIH, NTP or OSHA. Nota L – meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound using IP 346.
Reproductive toxicity	Not expected to have reproductive toxicity. Based on date for similar substances.
STOT-single exposure	Not expected to damage specific target organs. Based on date for similar substances.
STOT-repeated exposure	Not expected to damage specific target organs. Based on date for similar substances.
Aspiration hazard	The mixture does not meet the criteria for classification.
Other information	If material is misted or if vapours are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.

SECTION 12: Ecological information

	•	
12.1	Toxicity	This product is of relatively low toxicity – based on data of product components. LC ₅₀ for base oil (96 hours for fish) is > 100 mg/l (OECD 203) EC ₅₀ for base oils (48 hours for Daphnia) is > 10 000 mg/l (OECD 202) EC ₅₀ for base oils (72-96 hours for algae or other aquatic plants) > 100 mg/l (OECD 201) NOEL/21 days (aquatic invertebrates) > 10 mg/l (OECD 211) NOEL/72 h (algae) > 100 mg/l NOEL/10 min (micro organisms) > 1.93 mg/l (DIN 38412, DIN 38409)
12.2	Persistence and degradability	This product is not readily biodegradable. Information about base oil-Inherent biodegradability <22% after 28 days (OECD 301B).
12.3	Bioaccumulative potential	Partition coefficient n-octanol/water (log K _{ow}) for base oils is > 4.0 - indicates possible bioaccumulation.
12.4	Mobility in soil	Low, due to low water solubility. Spillage may penetrate the soil causing ground water contamination.
12.5	Results of PBT and vPvB asses	sment
12.0		This product is not and does not contain any substance that is potential PBT or vPvB.
12.6	Other adverse effects	May form an oil film leading to deoxygenation of water and possible harmful effect on aquatic life.
SECTIO	ON 13: Disposal consideratior	1
13.1	Waste treatment methods	Dispose of empty lubricant containers at approved for such wastes places. Follow all state or local regulations and requirements for disposal, recycle or reclaiming of waste oils and petroleum products.
	Waste Code	13 08 99* in accordance with European Waste Catalogue (E. W. C.)
SECTIO	ON 14: Transport information	
	•	

14.1	UN Number	None	
14.2	UN proper shipping name	Not applicable.	
	Version 1.07.11_EN		
	18.05.2018	ZAP Grease EXTREME VG 460 X1	Page: 6 of 8

14.3	Transport hazard class(es)	None
14.4	Packing group	Not applicable.
14.5	Environmental hazards	
	ADR	Not regulated as dangerous goods.
	RID	Not regulated as dangerous goods.
	AND	Not regulated as dangerous goods.
	IMDG	Not regulated as dangerous goods.
	IATA	Not regulated as dangerous goods.
14.6	Special precautions to user	None
14.7	Transport in bulk according t	o Annex II of Marpol and the IBC code Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of The European Parliament And Of The Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EC) No 1272/2008 of The European Parliament And Of The Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

15.2 Chemical safety assessment

Not available.

SECTION 16: Other information

Indication of which of the methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 was used for the purpose of classification.

Classification in accordance with regulation (EC) No 1272/2008:	Evaluation method used:
None.	Classification according to calculation procedure.
Revision Information Revision by sections Issue date	New SDS prepared according to Commission Regulation (EU) 2015/830. 18.05.2018
List of abbreviations	
PBT vPvB LD ₅₀	Persistent, Bioaccumulative, and Toxic very Persistent and very Bioaccumulative Lethal Dose 50 (median concentration of a toxicant that will kill 50% of the test animals within a designated period)

Version 1.07.11_EN 18.05.2018

ZAP Grease EXTREME VG 460 X1

LC ₅₀	Lethal Concentration 50 (concentration in water having 50% chance of causing				
	death to aquatic life)				
EC ₅₀	Half maximal effective concentration				
NOEL	No-Observed-Effect Level				
STOT	Specific Target Organ Toxicity				
A list of relevant hazard statements, hazard classes and category codes					
H315 - Causes skin irritation					
H317 - May cause an allergic skin reaction					
H319 - Causes serious eye irritation					

H412 - Harmful to aquatic life with long lasting effects Eye Irrit. 2 - Eye irritation, Hazard Category 2

Skin Irrit. 2 - Skin irritation, Hazard Category 2

Skin Sens. 1B - Sensitisation - Skin, Hazard category 1B

Aquatic Chronic 3 - Aquatic hazard (long-term) - Hazard Category 3

This information is the best of our current knowledge, and is believed to be correct as of the date hereof, and is intended to describe the product only in terms of health and safety and environmental requirements. Since the conditions of use are outside our control, any recommendations and suggestions are made without guarantee.

End of safety data sheet

